



MATERIAL SAFETY DATA SHEET
U.S. Department of Labor
Occupational Safety & Health Administration

CLEARCOAT 44

SECTION 1 - IDENTIFIERS

MANUFACTURER: Andek Corporation
ADDRESS: 850 Glen Avenue, Moorestown, NJ 08057
TELEPHONE: (856) 786-6900 or emergency (800) 424-9300 (CHEMTREC)
TRADE NAME: Clearcoat 44
CHEMICAL FAMILY: Urethane Prepolymer Solution

SECTION 2 – HAZARD IDENTIFICATION & EMERGENCY OVERVIEW

Emergency Overview: Toxic gases may be given off during burning or thermal decomposition. Closed container may forcibly rupture under extreme heat or when contents have been contaminated with water.

Effects of Overexposure:

SKIN: May cause dermal sensitization. May be absorbed through skin.

EYES: Contact may cause severe damage. Vapor may irritate.

BREATHING: Inhalation may cause headache, dizziness, nausea and irritation. Inhalation of spray mist may be toxic.

SWALLOWING: Harmful or fatal if swallowed.

SECTION 3 – COMPOSITION

COMPONENT	CAS #	APPROX %	TLV
Isophorone Diisocyanate Homopolymer	53880-05-0	43.0	N/A
Naptha, Light Aromatic Solvent	64742-95-6	46.0	N/A
Methyl Amyl Ketone	110-43-0	10.0	50.0ppm TWA
Isophorone Di-isocyanate	4098-71-9	<1.0	0.005 ppm TWA

KNOWN CARCINOGENS OR MUTAGENS - TYPE & DEFINITION_ - None known

SECTION 4 – FIRST AID MEASURES

SKIN: Clean thoroughly with waterless hand cleaner, followed by soap and water.

EYES: Flush with clear water for 15 minutes and seek immediate medical attention.

BREATHING: Move victim to fresh air and give artificial respiration or oxygen if needed.

SWALLOWING: Do NOT induce vomiting. Seek immediate medical attention.

SECTION 5 – FIRE & EXPLOSION HAZARD DATA

FLASH POINT (METHOD USED): 105°F. Closed Cup (ASTM D50).

FLAMMABLE LIMITS: Lel 0.9; Uel 6.0

EXTINGUISHING MEDIA: Carbon dioxide; dry chemical; foam.

SPECIAL FIRE FIGHTING PROCEDURES: If excessive fumes or smoke is encountered, wear self-contained breathing apparatus and full protective equipment.

UNUSUAL FIRE & EXPLOSION HAZARDS: Sealed containers may build up pressure if exposed to heat (fire). Water can be used to cool the exterior of the containers.

DECOMPOSITION PRODUCTS: Oxides of carbon, nitrogen, possible HCN and polyurethane combustion compounds.

SECTION 6 – SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

Cover with a layer of sand or other suitable absorbent. Use protective measures as outlined in Section 8 below. Avoid contact with skin, eyes and clothing.

SECTION 7 – HANDLING & STORAGE

CAUTION: Flammable liquid. Keep away from all sources of ignition. Use with adequate ventilation. Avoid prolonged or repeated contact with skin. Avoid contact with moisture. Store between 40°F and 80°F.

SECTION 8 – PERSONAL PROTECTION/EXPOSURE CONTROLS

RESPIRATORY PROTECTION (SPECIFY TYPE): In confined spaces use fresh air hood or NIOSH certified organic vapor canister unit. If used indoors, ventilate well using a general or local exhaust ventilation.

EYE PROTECTION: Wear chemical splash goggles or face shield. Do not wear contact lenses while working with this material.

SKIN PROTECTION: Nitrile rubber gloves to prevent skin contact.

OTHER PROTECTIVE EQUIPMENT: Coveralls and/or apron, rubber shoes or boots, eye wash station or fresh running water should be readily available.

PERSONAL HYGIENE: Wash hands thoroughly after handling and especially before eating or smoking. Shower at the end of work shift. Wash contaminated clothing before reuse.

SECTION 9 – PHYSICAL DATA

BOILING POINT (F)	312°	SPECIFIC GRAVITY (H2O=1)	0.93
VAPOR PRESSURE	10	PERCENT, VOLATILE BY VOLUME	56%
VAPOR DENSITY (AIR=1)	4.8	EVAPORATION RATE (N.B.A.=1)	0.25
SOLUBILITY IN WATER	Insoluble	pH (5% SLURRY)	Neutral

APPEARANCE & ODOR - Clear liquid with sweet, perfume-like odor.

SECTION 10 – REACTIVITY DATA

STABILITY: Stable.

INCOMPATIBILITY (MATERIALS TO AVOID): Water (moisture); alcohols; amines; strong acids and bases.

HAZARDOUS DECOMPOSITION PRODUCTS: Oxides of carbon and nitrogen, possible HCN and polyurethane combustion compounds.

HAZARDOUS POLYMERIZATION: Will not occur.

CONDITIONS TO AVOID: Excessive heat and/or wet conditions.

SECTION 11 – TOXICOLOGICAL INFORMATION

See reference data for individual components

SECTION 12 – ECOLOGICAL INFORMATION

See reference data for individual components

SECTION 13 – DISPOSAL CONSIDERATIONS

Dispose of in accordance with existing federal, state, and local environmental laws.

SECTION 14 – TRANSPORT INFORMATION

See reference data for individual components

SECTION 15 – REGULATORY INFORMATION

PROPER SHIPPING NAME: Paint

HAZARD CLASS: 3

PACKING GROUP: III

ID #: UN 1263

RQ: None

TRANSPORT LABELS REQUIRED: Flammable liquid.

SECTION 16 – OTHER INFORMATION (HMIS RATING)

Health	2
Flammability	2
Physical Hazard	1
Personal Protection	H

This information accumulated herein is believed to be accurate but is not warranted to be, whether originating with the company or not. Recipients are advised to confirm, in advance of need, that the information is current, applicable and suitable to their circumstances. Andek Corporation assumes no legal responsibility for use of or reliance upon the information contained in this MSDS.

DATE ISSUED: OCTOBER 2007