



MATERIAL SAFETY DATA SHEET
U.S. Department of Labor
Occupational Safety & Health Administration

ENCAPSALL SUPER

SECTION 1 - IDENTIFIERS

MANUFACTURER: Andek Corporation
ADDRESS: 850 Glen Avenue, Moorestown, NJ 08057
TELEPHONE: (856) 786-6900 or emergency (800) 424-9300 (CHEMTREC)
TRADE NAME: Encapsall Super
CHEMICAL FAMILY: Urethane Prepolymer Solution

SECTION 2 – HAZARD IDENTIFICATION & EMERGENCY OVERVIEW

Emergency Overview: Toxic gases may be given off during burning or thermal decomposition. Closed container may forcibly rupture under extreme heat or when contents have been contaminated with water.

Effects of Overexposure:

SKIN: Liquid may irritate skin.

EYES: Contact may cause severe damage; vapor may irritate.

BREATHING: Inhalation may cause headache, dizziness, nausea and irritation of respiratory tract.

SWALLOWING: May be harmful or fatal if swallowed.

SECTION 3 - COMPOSITION

COMPONENT	CAS #	APPROX %	TLV
Iron Oxide	1309-37-1	16.2	
Barium Sulfate	7727-43-7	13.8	
Naptha, Light Aromatic Solvent	64742-95-6	10.0	
Chlorinated Paraffin	8002-74-2	16.2	
Methylene Bisphenyl Isocyanate	101-68-8	2.8	
Polyether Prepolymer (Isocyanate Solution) boiling point <300°C; flash point >23°C	N.O.S.	31.5	
Aromatic Hydrocarbon Resin	64742-90-1	9.5	

KNOWN CARCINOGENS OR MUTAGENS - TYPE & DEFINITION – None known

SECTION 4 – FIRST AID MEASURES

SKIN: Clean thoroughly with waterless hand cleaner, then follow with soap and water.

EYES: Flush with water for 15 minutes and seek immediate medical attention.

BREATHING: Move victim to fresh air. If asthmatic conditions occur, call a physician.

SWALLOWING: Do NOT induce vomiting; seek immediate medical attention.

SECTION 5 – FIRE & EXPLOSION HAZARD DATA

FLASH POINT (METHOD USED): 108°F. Closed Cup (ASTM D50).

FLAMMABLE LIMITS: Lel 0.9; Uel 6.0.

EXTINGUISHING MEDIA: Carbon dioxide; dry chemical; foam.

SPECIAL FIRE FIGHTING PROCEDURES: If excessive fumes or smoke is encountered, wear self-contained respiratory equipment and full protective clothing.

UNUSUAL FIRE & EXPLOSION HAZARDS: Sealed containers may build up pressure if exposed to heat (fire). Water can be used to cool the exterior of the containers.

DECOMPOSITION PRODUCTS: Oxides of carbon, nitrogen, aluminum, possible HCN, polyurethane combustion compounds and halogens.

SECTION 6 – SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

Cover with a layer of sand or other suitable absorbent. Use protective measures as outlined under Section 8 below. Avoid contact with eyes, skin or clothing.

SECTION 7 – HANDLING & STORAGE

PRECAUTIONS TO BE TAKEN IN HANDLING:

Avoid contact with moisture. Isocyanates react with water and generate CO² which may rupture sealed containers. Store between 40° and 80°F.

SECTION 8 – PERSONAL PROTECTION/EXPOSURE CONTROLS

RESPIRATORY PROTECTION (SPECIFY TYPE): In confined spaces use fresh air hood or NIOSH certified organic vapor canister unit. If used outdoors, ventilate well using a general or local exhaust ventilation.

EYE PROTECTION: Wear chemical splash goggles or face shield. Do not wear contact lenses while working with this material.

SKIN PROTECTION: Nitrile rubber gloves and apply a solvent-resistant barrier cream to areas of skin that may come in contact with this material.

OTHER PROTECTIVE EQUIPMENT: Eye wash station or fresh running water should be readily available. Wear coveralls and/or rubber apron and rubber shoes or boots.

PERSONAL HYGIENE: Wash hands thoroughly after handling and especially before eating or smoking. Shower at the end of the work shift. Wash contaminated clothing before reuse.

SECTION 9 – PHYSICAL DATA

BOILING POINT (F)	312°	SPECIFIC GRAVITY (H2O=1)	1.2
VAPOR PRESSURE	10	PERCENT, VOLATILE BY VOLUME	18.0
VAPOR DENSITY (AIR=1)	<4.8	EVAPORATION RATE (N.B.A.=1)	0.2
SOLUBILITY IN WATER	Insoluble	pH (5% SLURRY)	Neutral

APPEARANCE & ODOR - Black liquid with aromatic solvent odor.

SECTION 10 – REACTIVITY DATA

STABILITY: Stable.

INCOMPATABILITY (MATERIALS TO AVOID): Water (moisture); alcohols; amines; strong acids and bases.

HAZARDOUS DECOMPOSITION PRODUCTS: Possible HCN.

HAZARDOUS POLYMERIZATION: Will not occur.

CONDITIONS TO AVOID: Contamination with water will evolve CO².

SECTION 11 – TOXICOLOGICAL INFORMATION

See reference data for individual components

SECTION 12 – ECOLOGICAL INFORMATION

See reference data for individual components

SECTION 13 – DISPOSAL CONSIDERATIONS

Dispose of in accordance with existing federal, state, and local environmental laws.

SECTION 14 – TRANSPORT INFORMATION

PROPER SHIPPING NAME: Paint

HAZARD CLASS: 3

PACKING GROUP: III

ID #: UN 1263

RQ: None

TRANSPORT LABELS REQUIRED: Flammable liquid. (In the U.S., this material may be re-classified as a combustible liquid and is not regulated in containers less than 119 gallons via surface transportation.)

SECTION 15 – REGULATORY INFORMATION

See reference data for individual components

SECTION 16 – OTHER INFORMATION (HMIS RATING)

Health	2
Flammability	2
Physical Hazard	1
Personal Protection	H

This information accumulated herein is believed to be accurate but is not warranted to be, whether originating with the company or not. Recipients are advised to confirm, in advance of need, that the information is current, applicable and suitable to their circumstances. Andek Corporation assumes no legal responsibility for use of or reliance upon the information contained in this MSDS.

DATE ISSUED: OCTOBER 2007