



MATERIAL SAFETY DATA SHEET
U.S. Department of Labor
Occupational Safety & Health Administration

POLASEAL EFM

SECTION 1 - IDENTIFIERS

MANUFACTURER: Andek Corporation
ADDRESS: 850 Glen Avenue, Moorestown, NJ 08057
TELEPHONE: (856) 786-6900 or emergency (800) 424-9300 (CHEMTREC)
TRADE NAME: Polaseal EFM
CHEMICAL FAMILY: Water-Based Siloxane Emulsion

SECTION 2 – HAZARD IDENTIFICATION & EMERGENCY OVERVIEW

Emergency Overview: Not considered to be hazardous. Some individuals may find the odor to be unpleasant.

Effects of Overexposure:

SKIN: Mild skin irritant.

EYES: Very irritating to the eyes.

BREATHING: Mists may cause irritation to the upper respiratory tract.

SWALLOWING: Harmful if swallowed.

SECTION 3 - COMPOSITION

COMPONENT	CAS #	APPROX %	TLV
PolyDimethyl Siloxane w/Amino Functional Groups	9043-30-5	10.0	
Fungicide: MgNO2 CuNO2 MgCC2	10377-60-3 3251-23-8 10034-81-8	0.3	
Nochar N.F.P.	Trade secret	9.3	
Water	7732-18-5	80.0	
Ammonium Hydroxide	7664-41-7	0.4	

KNOWN CARCINOGENS OR MUTAGENS - TYPE & DEFINITION – None known

SECTION 4 – FIRST AID MEASURES

SKIN: Wash area with soap and water.

EYES: Flush eyes with clear water for 15 minutes and seek immediate medical attention.

BREATHING: Move victim to fresh air and apply appropriate first aid.

SWALLOWING: Do NOT induce vomiting. Immediately contact a physician. Dilute contents of stomach with 3-4 glasses of milk or water.

SECTION 5 – FIRE & EXPLOSION HAZARD DATA

FLASH POINT (METHOD USED): 200°F (Seta).

FLAMMABLE LIMITS: N/A

EXTINGUISHING MEDIA: Dry chemical; carbon dioxide; foam; water.

SPECIAL FIRE FIGHTING PROCEDURES: Fire fighters should wear positive pressure self-contained breathing apparatus.

UNUSUAL FIRE & EXPLOSION HAZARDS: None

DECOMPOSITION PRODUCTS: Thermal decomposition yields oxides of C, N, Ca, Si, Ba and Halides.

SECTION 6 – SPILL OR LEAK PROCEDURES

Ventilate area, absorb with absorbent material. Place in approved waste disposal container.

SECTION 7 – HANDLING & STORAGE

Keep container tightly closed when not in use. Protect from freezing.

SECTION 8 – PERSONAL PROTECTION/EXPOSURE CONTROLS

RESPIRATORY PROTECTION (SPECIFY TYPE): If ventilation is inadequate, use a respirator with dust/mist/fume cartridges.

EYE PROTECTION: Splash-proof chemical goggles.

SKIN PROTECTION: Rubber gloves.

OTHER PROTECTIVE EQUIPMENT: Coveralls.

PERSONAL HYGIENE: Wash thoroughly after use.

SECTION 9 - PHYSICAL DATA

BOILING POINT (F)	218°	SPECIFIC GRAVITY (H20=1)	1.0
VAPOR PRESSURE	20	PERCENT, VOLATILE BY VOLUME	80.4
VAPOR DENSITY (AIR=1)	1	EVAPORATION RATE (N.B.A.=1)	1
SOLUBILITY IN WATER	Soluble	pH	Approx. 7.5

APPEARANCE & ODOR - Opaque milky liquid with mildly ammoniacal odor.

SECTION 10 – REACTIVITY DATA

STABILITY: Stable.

INCOMPATIBILITY (MATERIALS TO AVOID): Strong oxidizers.

HAZARDOUS POLYMERIZATION: Will not occur.

CONDITIONS TO AVOID: Freezing.

SECTION 11 – TOXICOLOGICAL INFORMATION

See reference data for individual components.

SECTION 12 – ECOLOGICAL INFORMATION

See reference data for individual components.

SECTION 13 – DISPOSAL CONSIDERATIONS

Dispose of in according to local, state and federal regulations.

SECTION 14 - TRANSPORT INFORMATION

PROPER SHIPPING NAME: Waterproofing compound

HAZARD CLASS: None

PACKING GROUP: N/A

ID #: N/A

RQ: N/A

TRANSPORT LABELS REQUIRED: This material is not regulated by the D.O.T.

SECTION 15 – REGULATORY INFORMATION

See reference data for individual components.

SECTION 16 – OTHER INFORMATION (HMIS RATING)

Health	1
Flammability	0
Physical Hazard	0
Personal Protection	B

This information accumulated herein is believed to be accurate but is not warranted to be, whether originating with the company or not. Recipients are advised to confirm, in advance of need, that the information is current, applicable and suitable to their circumstances. Andek Corporation assumes no legal responsibility for use of or reliance upon the information contained in this MSDS.

DATE ISSUED: OCTOBER 2007