

**MATERIAL SAFETY DATA SHEET**  
U.S. Department of Labor  
Occupational Safety & Health Administration

## COCOON 72634 USDA

### **SECTION 1 - IDENTIFIERS**

MANUFACTURER: Andek Corporation  
 ADDRESS: 850 Glen Avenue, Moorestown, NJ 08057  
 TELEPHONE: 1-856-786-6900  
 In an emergency, contact CHEMTREC 1-800- 424-9300;  
 Outside the United States call +1-703-527-3887  
 TRADE NAME: Cocoon 72634 USDA

### **SECTION 2 – HAZARD IDENTIFICATION & EMERGENCY OVERVIEW**

**Emergency Overview:** Toxic gases may be given off during burning or thermal decomposition. Closed containers may forcibly rupture under extreme heat.

#### **Effects of Overexposure:**

SKIN: Frequent or prolonged contact may irritate and cause dermatitis. Low order toxicity.

EYES: Irritating and will injure eye tissue if not removed promptly; vapors may irritate eyes.

BREATHING: High vapor concentrations are irritating to the eyes and the respiratory tract, may cause headaches, drowsiness, and dizziness; are anesthetic or narcotic and may have other central nervous system effects.

SWALLOWING: Minimal toxicity. Small amounts of the liquid aspirated into the respiratory system during ingestion, or from vomiting, may cause bronchopneumonia or pulmonary edema; no hazards anticipated from ingestion incidental to industrial exposure.

### **SECTION 3 - COMPOSITION**

COMPONENT	CAS #	APPROX %	TLV
Toluene	108-88-3	28.0	
Butene Dioic Acid Polymer w/Chloroethene and Ethenyl Acetate	9005-09-8	29.6	
Acetone	67-64-1	42.0	
Vinyl Acetate	108-06-4	0.2	
Methyl Isobutyl Ketone	108-10-1	0.2	

KNOWN CARCINOGENS OR MUTAGENS: Vinyl Acetate – IARC possible carcinogen; 2B

### **SECTION 4 – FIRST AID MEASURES**

SKIN: Immediately flush with large amounts of water; use soap if available; remove contaminated clothing, including shoes, after flushing has begun.

EYES: Immediately flush eyes with large amounts of water for at least 15 minutes; get prompt medical attention.

BREATHING: Using proper respiratory protection, immediately remove the affected victim from exposure; administer artificial respiration if breathing has stopped; keep at rest; get prompt medical attention.

SWALLOWING: First aid is not normally required; induce vomiting if large quantity is ingested; call a physician.

### **SECTION 5 – FIRE & EXPLOSION HAZARD DATA**

FLASH POINT (METHOD USED): 0°F. TCC

FLAMMABLE LIMITS: None LEL: 3% UEL: 12%

EXTINGUISHING MEDIA: Carbon dioxide or dry chemical

SPECIAL FIRE FIGHTING PROCEDURES: Do not use water or soda acid. Use respiratory protection.

UNUSUAL FIRE & EXPLOSION HAZARDS: Explosion limits approximately 3% to 12%. Handle similar to fighting Toluene or Ketone fire.

### **SECTION 6 – SPILL OR LEAK PROCEDURES**

Clean up immediately. If spill is excessive, ventilate area. No smoking, open flame, sparks, etc.

### **SECTION 7 – HANDLING & STORAGE**

Store in cool place in closed containers away from fire hazards. Post NO SMOKING, NO WELDING, NO OPEN FLAME signs in work area.

**SECTION 8 – PERSONAL PROTECTION/EXPOSURE CONTROLS**

RESPIRATORY PROTECTION: Organic vapor respirator or fresh air hood. Ventilate work area properly.

VENTILATION: Portable explosion proof fans. No smoking, open flame, sparks, or excessive heat.

PROTECTIVE GLOVES: Not required. Non-static, chemical resistant, if desired.

EYE PROTECTION: Not required. Goggles or safety glasses, if desired.

PROTECTIVE CLOTHING: Non-static clothing and shoes.

WORK/HYGIENIC PRACTICES: Wash with soap and water.

**SECTION 9 - PHYSICAL DATA**

BOILING POINT (F)	149°F	SPECIFIC GRAVITY (H <sub>2</sub> O=1)	.91
VAPOR PRESSURE	N/A	MELTING POINT	N/A
VAPOR DENSITY (AIR=1)	Heavier	EVAPORATION RATE (N.B.A.=1)	4.5
SOLUBILITY IN WATER	Slight	V.O.C.	2.12 lb/gal - 254 g/l

APPEARANCE & ODOR - Lacquers, Ketone Solvents (nail polish)

**SECTION 10 - REACTIVITY DATA**

STABILITY: Stable.

HAZARDOUS DECOMPOSITION OR BY- PRODUCTS: Unknown. Possibly slight amounts of HCL, carbon dioxide, and some carbon monoxide.

HAZARDOUS POLIMERIZATION: Will not occur.

CONDITIONS TO AVOID: Keep away from oxidizing agents and open flame when containers are open.

MATERIALS TO AVOID: Oxidizing agents.

**SECTION 11 – TOXICOLOGICAL INFORMATION**

See reference data for individual components.

**SECTION 12 – ECOLOGICAL INFORMATION**

See reference data for individual components.

**SECTION 13 – DISPOSAL CONSIDERATIONS**

Dispose of in accordance with existing federal, state and local environmental laws.

**SECTION 14 – TRANSPORT INFORMATION**

PROPER SHIPPING NAME:	Paint
HAZARD CLASS:	3
PACKING GROUP:	2
ID #:	UN 1263
RQ:	None

TRANSPORT LABELS REQUIRED: Flammable liquid

**SECTION 15 – REGULATORY INFORMATION**

See reference data for individual components.

**SECTION 16 – OTHER INFORMATION (HMIS RATING)**

Health	2
Flammability	3
Physical Hazard	1
Personal Protection	H

**Disclaimer:** Andek Corporation (Andek) believes, to the best of its knowledge, information and belief, the information contained herein to be accurate and reliable as of the issue date of this Material Safety Data Sheet (MSDS). However, because the conditions of handling, use, and storage of these materials are beyond Andek's control, we assume no responsibility or liability for personal injury or property damage incurred by the use of these materials and make no warranty, expressed or implied, regarding the accuracy or reliability of the data or results obtained from their use. All materials may present unknown hazards and should be used with caution. The information and recommendations contained in this MSDS are offered for the users' consideration and examination. It is the responsibility of the user to determine the final suitability of this information and data and to comply with all applicable international, federal, state, and local laws and regulations.