

# AIM #3™

## Vapor Retarder



**DESCRIPTION**

AIM #3 is a premium quality, single component waterproofing coating that is especially designed to waterproof building foundations. It is resistant to sulfates, soil contaminants, bacteria, and other environmental conditions. AIM #3 is designed for permanent flexibility and toughness, to bridge and move with hairline cracks, and to resist impingement attack.

**OUTSTANDING FEATURES**

- ✓ Sets quickly and begins to cure immediately after application
- ✓ Remains flexible and tough
- ✓ Highly penetrative and workable
- ✓ Extremely durable and waterproof
- ✓ Prevents damage from water, even under ponded conditions
- ✓ Possesses a 20-year life expectancy
- ✓ Can be applied at any temperature; not affected by sudden rain

**APPLICATION**

Caution! Read this entire product data sheet before continuing.

Surfaces to be coated must be dry and free of loose debris, dirt, oil, grease, or any substance

bond. AIM #3 may be applied straight from the container after 2 minutes of low speed mechanical stirring. Apply the product using brush, roller, or airless spray technique. If airless spray application is desired, a custom blended AIM #3 version is available to be used with the following equipment: ratio 30:1 or 40:1 with a 1/2" or 3/4" hose and a #35 or larger tip. A shorter hose will increase output at the tip.

Apply AIM #3 in a smooth, even fashion to achieve a uniform coating thickness in either 1 or 2 coats. Equipment may be cleaned with xylene or toluene before AIM #3 begins to dry.

**LIMITATIONS**

Do not apply to wet or frozen surfaces that are saturated with moisture. Proper surface preparation and priming where indicated are important to product

performance. Shelf life is 12 months when stored indoors in factory sealed containers. This product is combustible. Keep away from heat, sparks, and flames. Use only EP rated equipment.

**PRECAUTIONS**

This product contains solvent. Avoid contact with skin and eyes. In case of contact with skin, wash with soap and water for 15 minutes. In case of contact with eyes, flush with water for 15 minutes and seek immediate medical attention. Do not ingest. In case of ingestion, do NOT induce vomiting and contact a physician. Avoid inhalation of fumes. If aerosol mist is inhaled, immediately seek medical attention. Wear safety goggles, rubber gloves, coveralls, and filter mask when applying this product.

SPECIFICATIONS	
Coating Type	Ethylene elastomer
VOC:	450 gms/liter
Pot Life:	Single Component
Shelf Life:	12 months
Recommended Thickness:	25 mils dry film thickness
Coverage:	40 square feet per gallon
Packaging:	5 U.S. gallons (standard size)
Color:	White & other colors

PRODUCT DATA

**AIM #3**™  
**Vapor Retarder**



TECHNICAL DATA		
<b>Moisture Vapor Transmission</b>	0.01 perms	ASTM E-96
<b>Tensile Strength</b>	864 psi	ASTM D-412
<b>Elongation</b>	550%	ASTM D-412
<b>Solids Content</b>	63% (B.W.); 55% (B.V.)	ASTM D-1044
<b>Shore 'A' Hardness</b>	75	ASTM D-2240
<b>Weatherometer (5000 hours)</b>	Pass	ASTM G-23
<b>Density</b>	Approx. 9 lb/gallon	
<b>Viscosity</b>	Approx. 15,000 cps	
<b>Low Temperature Flexibility</b>	180° bend @ 10°F	
<b>Flashpoint (closed cup)</b>	105° F	FTMS 141A(M4293)

NOTICE: The information presented herein is based on tests and data that Andek Corporation believes to be reliable. It is intended for use by technically qualified personnel at their own discretion and risk. Since conditions of handling and use are beyond our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information. Nothing herein is to be construed as a license to operate or a recommendation to infringe any patent.

Effective Date: 02/2009

© 2009 Andek Corporation. All right reserved. ANDEK is a registered trademark

**ANDEK CORPORATION** · 850 Glen Ave · P.O. Box 392 · Moorestown NJ 08057-0392  
Tel: (800) 800-2844 · Fax: (856) 786-0580 · www.Andek.com