



MATERIAL SAFETY DATA SHEET
U.S. Department of Labor
Occupational Safety & Health Administration

WEARCOAT 66 (Part B)

SECTION 1 - IDENTIFIERS

MANUFACTURER: Andek Corporation
ADDRESS: 850 Glen Avenue, Moorestown, NJ 08057
TELEPHONE: (856) 786-6900 or emergency (800) 424-9300 (CHEMTREC)
TRADE NAME: Wearcoat 66 Part B
CHEMICAL FAMILY: Acrylic/Pigment Dispersion

SECTION 2 – HAZARD IDENTIFICATION & EMERGENCY OVERVIEW

Emergency Overview: Particulates, ashes and soot may be emitted during burning or incomplete combustion. Closed container may rupture under extreme heat.

Effects of Overexposure:

SKIN: Irritant to skin. Prolonged or repeated contact may cause defatting and/or dermatitis.

EYES: Direct contact may cause burning, tearing, redness or swelling.

BREATHING: Irritant to respiratory tract. Prolonged breathing of vapors may cause headache, dizziness, or nausea.

SWALLOWING: May cause irritation of the digestive tract; drowsiness; dizziness; loss of coordination; fatigue.

SECTION 3 - COMPOSITION

COMPONENT	CAS #	APPROX %	TLV
Titanium Dioxide	13463-67-7	65.0	
Aldehyde Resin	2110-1200-0	15.0	
Aromatic 100	64742-95-6	10.0	
PM Acetate	108-65-6	10.0	

KNOWN CARCINOGENS OR MUTAGENS - TYPE & DEFINITION – None known

SECTION 4 – FIRST AID MEASURES

SKIN: Wash well with soap and water; remove contaminated clothing and wash before reuse.

EYES: Flush eyes with clear water for 15 minutes. Get immediate medical attention.

BREATHING: Remove victim to fresh air, away from vapors.

SWALLOWING: Do NOT induce vomiting. Get medical attention immediately.

SECTION 5 – FIRE & EXPLOSION HAZARD DATA

FLASH POINT (METHOD USED): 108°F

FLAMMABLE LIMITS: 1.0/6.0

EXTINGUISHING MEDIA: Water fog; carbon dioxide; dry chemical

SPECIAL FIRE FIGHTING PROCEDURES: Do not use water, except as foam.

UNUSUAL FIRE & EXPLOSION HAZARDS: Keep away from excessive heat or open flame.

DECOMPOSITION PRODUCTS: Combustion will produce carbon dioxide and possibly carbon monoxide.

SECTION 6 – SPILL OR LEAK PROCEDURES

Cover with a layer of sand or other suitable absorbent. Use protective measures as outlined in Section 8 below. Avoid contact with skin, eyes and clothing.

SECTION 7 – HANDLING & STORAGE

CAUTION: flammable liquid. Keep away from all sources of ignition. Use with adequate ventilation. Avoid prolonged or repeated contact with skin. Avoid contact with moisture.

SECTION 8 – PERSONAL PROTECTION/EXPOSURE CONTROLS

RESPIRATORY PROTECTION (SPECIFY TYPE): In confined spaces, use fresh air hood or NIOSH certified organic vapor canister unit. If used indoors, ventilate well using a general or local exhaust ventilation.

EYE PROTECTION: Wear chemical splash goggles or face shield. Do not wear contact lenses while working with this material.

SKIN PROTECTION: Nitrile rubber gloves to prevent skin contact.

OTHER PROTECTIVE EQUIPMENT: Coveralls and/or apron, rubber shoes or boots, eye wash station or fresh running water should be readily available.

PERSONAL HYGIENE: Wash hands thoroughly after handling and especially before eating or smoking. Shower at the end of work shift. Wash contaminated clothing before reuse.

SECTION 9 - PHYSICAL DATA

BOILING POINT (F)	280°-350°	SPECIFIC GRAVITY (H20=1)	1.89
VAPOR PRESSURE	2.1	PERCENT, VOLATILE BY VOLUME	20
VAPOR DENSITY (AIR=1)	4.4	EVAPORATION RATE (N.B.A.=1)	<1.0
SOLUBILITY IN WATER	Insoluble	pH	N/A

APPEARANCE & ODOR - Paste; acetate odor – Color will vary

SECTION 10 - REACTIVITY DATA

STABILITY: Stable

INCOMPATIBILITY (MATERIALS TO AVOID): Keep away from excessive heat and open flames.

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon dioxide and possibly carbon monoxide.

HAZARDOUS POLYMERIZATION: Will not occur.

CONDITIONS TO AVOID: Excessive heat and open flames.

SECTION 11 – TOXICOLOGICAL INFORMATION

See reference data for individual components.

SECTION 12 – ECOLOGICAL INFORMATION

See reference data for individual components.

SECTION 13 – DISPOSAL CONSIDERATIONS

Dispose of in accordance with local, state and federal regulations.

SECTION 14 – TRANSPORT INFORMATION

PROPER SHIPPING NAME: Paint

HAZARD CLASS: 3

PACKING GROUP: III

ID #: UN 1263

RQ: None


TRANSPORT LABELS REQUIRED: Flammable liquid. (In the U.S., this material may be re-classified as a combustible liquid and is not regulated in containers less than 119 gallons via surface transportation.)

SECTION 15 – REGULATORY INFORMATION

See reference data for individual components.

SECTION 16 – OTHER INFORMATION (HMIS RATING)

Health	1
Flammability	2
Physical Hazard	0
Personal Protection	G

This information accumulated herein is believed to be accurate but is not warranted to be, whether originating with the company or not. Recipients are advised to confirm, in advance of need, that the information is current, applicable and suitable to their circumstances. Andek Corporation assumes no legal responsibility for use of or reliance upon the information contained in this MSDS. 

DATE ISSUED: OCTOBER 2007