



MATERIAL SAFETY DATA SHEET
U.S. Department of Labor
Occupational Safety & Health Administration

POLAPRIME 2

SECTION 1 - IDENTIFIERS

MANUFACTURER: Andek Corporation
ADDRESS: 850 Glen Avenue, Moorestown, NJ 08057
TELEPHONE: (856) 786-6900 or emergency (800) 424-9300 (CHEMTREC)
TRADE NAME: Polaprime 2
CHEMICAL FAMILY: Acrylic Copolymer Emulsion

SECTION 2 – HAZARD IDENTIFICATION & EMERGENCY OVERVIEW

Emergency Overview: Not considered to be hazardous. Some individuals may find the odor to be unpleasant.

Effects of Overexposure:

SKIN: May irritate skin.

EYES: Contact is unpleasant; vapor may irritate.

BREATHING: Not considered harmful; slight ammoniacal odor may annoy some individuals.

SWALLOWING: Although non-toxic, entry into throat may cause choking.

SECTION 3 - COMPOSITION

COMPONENT	CAS #	APPROX %	TLV
Calcium Silicate	1344-95-2	10.0	
Calcium Carbonate	75-20-7	1.7	
Barium Metaborate Monohydrate	13701-59-2	4.5	
Dispersant (nonionic)/Defoamer (Silicon Emulsion) Acrylic Copolymer and Polyvinyl Diene Chloride/	744-21-3	0.5	
Ethylene Acetate	25085-46-5	49.9	
Water	7732-18-5	Balance	

KNOWN CARCINOGENS OR MUTAGENS - TYPE & DEFINITION – None known

SECTION 4 – FIRST AID MEASURES

SKIN: While wet, wash with water. If dry, use proprietary hand cleaner, followed by hot water.

EYES: Flush with plenty of water and seek medical attention.

BREATHING: Remove to fresh air.

SWALLOWING: Induce vomiting and call a physician.

SECTION 5 – FIRE & EXPLOSION HAZARD DATA

FLASH POINT (METHOD USED): >200°F (ASTM D50).

FLAMMABLE LIMITS: N/A

EXTINGUISHING MEDIA: N/A

SPECIAL FIRE FIGHTING PROCEDURES: N/A

UNUSUAL FIRE & EXPLOSION HAZARDS: None

DECOMPOSITION PRODUCTS: Oxides of carbon, barium, boron, calcium, silicon, and halogens.

SECTION 6 – SPILL OR LEAK PROCEDURES

Cover with a layer of sand or suitable absorbent material or wash away with water.

SECTION 7 – HANDLING & STORAGE

Avoid prolonged contact with skin. Do not consume food or beverage while handling. Do not allow to freeze; otherwise material will be unusable and require disposal.

SECTION 8 – PERSONAL PROTECTION/EXPOSURE CONTROLS

RESPIRATORY PROTECTION (SPECIFY TYPE): Unnecessary if used outdoors.

EYE PROTECTION: Chemical splash goggles.

SKIN PROTECTION: Neoprene rubber or polyethylene gloves.

OTHER PROTECTIVE EQUIPMENT: Coveralls and/or rubber apron, rubber shoes or boots.

PERSONAL HYGIENE: Wash thoroughly after use.

SECTION 9 - PHYSICAL DATA

BOILING POINT (F)	212°	SPECIFIC GRAVITY (H2O=1)	0.95
VAPOR PRESSURE	68	PERCENT, VOLATILE BY VOLUME	65
VAPOR DENSITY (AIR=1)	As Water	EVAPORATION RATE (N.B.A.=1)	1.0
SOLUBILITY IN WATER	100%	pH	8.0

APPEARANCE & ODOR - White liquid with an ammoniacal odor.

SECTION 10 – REACTIVITY DATA

STABILITY: Stable.

INCOMPATIBILITY (MATERIALS TO AVOID): Strong oxidizers.

HAZARDOUS DECOMPOSITION PRODUCTS: None

HAZARDOUS POLYMERIZATION: Will not occur.

CONDITIONS TO AVOID: Freezing will coagulate material.

SECTION 11 – TOXICOLOGICAL INFORMATION

See reference data for individual components.

SECTION 12 – ECOLOGICAL INFORMATION

See reference data for individual components.

SECTION 13 – DISPOSAL CONSIDERATIONS

Dispose of in accordance with local, state and federal regulations.

SECTION 14 – TRANSPORT INFORMATION

PROPER SHIPPING NAME: Paint

HAZARD CLASS: None

PACKING GROUP: N/A

ID #: N/A

RQ: N/A

TRANSPORT LABELS REQUIRED: This material is not regulated by the D.O.T.

SECTION 15 – REGULATORY INFORMATION

See reference data for individual components.

SECTION 16 – OTHER INFORMATION (HMIS RATING)

Health	1
Flammability	0
Physical Hazard	0
Personal Protection	B

This information accumulated herein is believed to be accurate but is not warranted to be, whether originating with the company or not. Recipients are advised to confirm, in advance of need, that the information is current, applicable and suitable to their circumstances. Andek Corporation assumes no legal responsibility for use of or reliance upon the information contained in this MSDS.

REVISED: OCTOBER 2007