



**MATERIAL SAFETY DATA SHEET**  
U.S. Department of Labor  
Occupational Safety & Health Administration

**ROOFDX SUPER**

**SECTION 1 – IDENTIFIER**

MANUFACTURER: Andek Corporation  
ADDRESS: 850 Glen Avenue, Moorestown, NJ 08057  
TELEPHONE: (856) 786-6900 or emergency (800) 424-9300 (CHEMTREC)  
TRADE NAME: RoofdX Super  
CHEMICAL FAMILY: Urethane Prepolymer Solution

**SECTION 2 – HAZARD IDENTIFICATION & EMERGENCY OVERVIEW**

Emergency Overview: Toxic gases may be given off during burning or thermal decomposition. Closed container may forcibly rupture under extreme heat or when contents have been contaminated with water.

Effects of Overexposure:

SKIN: Liquid may irritate skin.

EYES: Contact may cause severe damage; vapor may irritate.

BREATHING: Inhalation may cause headache, dizziness, nausea and irritation of respiratory tract.

SWALLOWING: May be harmful or fatal if swallowed.

**SECTION 3 - COMPOSITION**

COMPONENT	CAS #	APPROX %	TLV
Iron Oxide	1309-37-1	16.2	
Barium Sulfate	7727-43-7	13.8	
Naptha, Light Aromatic Solvent	64742-95-6	10.0	
Chlorinated Paraffin	8002-74-2	16.2	
Methylene Bisphenyl Isocyanate	101-68-8	2.8	
Polyether Prepolymer (Isocyanate Solution) boiling point <300°C; flash point >23°C	N.O.S.	31.5	
Aromatic Hydrocarbon Resin	64742-90-1	9.5	

KNOWN CARCINOGENS OR MUTAGENS - TYPE & DEFINITION - None known.

#### SECTION 4 - FIRST AID MEASURES

---

SKIN: Clean thoroughly with waterless hand cleaner, then follow with soap and water.

EYES: Flush with water for 15 minutes and seek immediate medical attention.

BREATHING: Move victim to fresh air. If asthmatic conditions occur, call a physician.

SWALLOWING: Do NOT induce vomiting. Seek immediate medical attention.

#### SECTION 5 - FIRE & EXPLOSION HAZARD DATA

---

FLASH POINT (METHOD USED): 108°F. Closed Cup (ASTM D50).

FLAMMABLE LIMITS: Lel 0.9; Uel 6.0.

EXTINGUISHING MEDIA: Carbon dioxide; dry chemical; foam.

SPECIAL FIRE FIGHTING PROCEDURES: If excessive fumes or smoke is encountered, wear self-contained respiratory equipment and full protective clothing.

UNUSUAL FIRE & EXPLOSION HAZARDS: Sealed containers may build up pressure if exposed to heat (fire). Water can be used to cool the exterior of the containers.

DECOMPOSITION PRODUCTS: Oxides of carbon, nitrogen, aluminum, possible HCN, polyurethane combustion compounds and halogens.

#### SECTION 6 - SPILL OR LEAK PROCEDURES

---

Cover with a layer of sand or other suitable absorbent. Use protective measures as outlined under Section 8 below. Avoid contact with eyes, skin or clothing.

#### SECTION 7 - HANDLING & STORAGE

---

Avoid contact with moisture. Isocyanates react with water and generate CO<sup>2</sup> which may rupture sealed containers. Store between 40 and 80°F.

#### SECTION 8 - PERSONAL PROTECTION/EXPOSURE CONTROLS

---

RESPIRATORY PROTECTION (SPECIFY TYPE): In confined spaces use fresh air hood or NIOSH certified organic vapor canister unit. If used outdoors, ventilate well using a general or local exhaust ventilation.

EYE PROTECTION: Wear chemical splash goggles or face shield. Do not wear contact lenses while working with this material.

SKIN PROTECTION: Nitrile rubber gloves and apply a solvent-resistant barrier cream to areas of skin that may come in contact with this material.

OTHER PROTECTIVE EQUIPMENT: Eye wash station or fresh running water should be readily available. Wear coveralls and/or rubber apron and rubber shoes or boots.

PERSONAL HYGIENE: Wash hands thoroughly after handling and especially before eating or smoking. Shower at the end of the work shift. Wash contaminated clothing before reuse.

#### SECTION 9 - PHYSICAL DATA

---

<b>BOILING POINT (F)</b>	312°	<b>SPECIFIC GRAVITY (H<sub>2</sub>O=1)</b>	1.2
<b>VAPOR PRESSURE</b>	10	<b>PERCENT, VOLATILE BY VOLUME</b>	13.7
<b>VAPOR DENSITY (AIR=1)</b>	<4.8	<b>EVAPORATION RATE (N.B.A.=1)</b>	0.2
<b>SOLUBILITY IN WATER</b>	Insoluble	<b>pH (5% SLURRY)</b>	Neutral

APPEARANCE & ODOR - Black liquid with aromatic solvent odor.

## **SECTION 10 - REACTIVITY DATA**

---

STABILITY: Stable.

INCOMPATIBILITY (MATERIALS TO AVOID): Water (moisture); alcohols; amines; strong acids and bases.

HAZARDOUS DECOMPOSITION PRODUCTS: Possible HCN.

HAZARDOUS POLYMERIZATION: Will not occur.

CONDITIONS TO AVOID: Contamination with water will evolve CO<sup>2</sup>.

## **SECTION 11 - TOXICOLOGICAL INFORMATION**

---

See reference data for individual components.

## **SECTION 12 - ECOLOGICAL INFORMATION**

---

See reference data for individual components.

## **SECTION 13 - DISPOSAL CONSIDERATIONS**

---

Dispose of in accordance with local, state and federal regulations.

## **SECTION 14 - TRANSPORT INFORMATION**

---

PROPER SHIPPING NAME: Paint

HAZARD CLASS: 3

PACKING GROUP: III

ID #: UN 1263

RQ: None

TRANSPORT LABELS REQUIRED: Flammable liquid. (In the U.S., this material may be re-classified as a combustible liquid and is not regulated in containers less than 119 gallons via surface transportation.)

## **SECTION 15 - REGULATORY INFORMATION**

---

See reference data for individual components.

## **SECTION 16 - OTHER INFORMATION (HMIS RATING)**

---

Health	2
Flammability	2
Physical Hazard	1
Personal Protection	H

This information accumulated herein is believed to be accurate but is not warranted to be, whether originating with the company or not. Recipients are advised to confirm, in advance of need, that the information is current, applicable and suitable to their circumstances.

DATE ISSUED: OCTOBER 2007