



MATERIAL SAFETY DATA SHEET
U.S. Department of Labor
Occupational Safety & Health Administration

'T' CATALYST

SECTION 1 – IDENTIFIER

MANUFACTURER: Andek Corporation
ADDRESS: 850 Glen Avenue, Moorestown, NJ 08057
TELEPHONE: (856) 786-6900 or emergency (800) 424-9300 (CHEMTREC)
TRADE NAME: 'T' Catalyst
CHEMICAL FAMILY: Complex Alkanolamine Titanate

SECTION 2 – HAZARD IDENTIFICATION & EMERGENCY OVERVIEW

Emergency Overview: Not considered to be hazardous. Some individuals may find the odor to be unpleasant.

Effects of Overexposure:

SKIN: May cause skin irritation.

EYES: May cause redness, swelling and tearing of the eyes. Vapor may irritate.

BREATHING: May cause irritation to the upper respiratory tract.

SWALLOWING: Highly damaging to the digestive tissue lining. Harmful or fatal if swallowed.

SECTION 3 - COMPOSITION

COMPONENT	CAS #	APPROX %	TLV
Complex Alkanolame Titanate	68784-47-4	60	
Diethylene Glycol	111-46-6	38	
Naptha	64742-49-0	1	
Isopropanol	67-63-0	1	

KNOWN CARCINOGENS OR MUTAGENS - TYPE & DEFINITION – None known

SECTION 4 – FIRST AID MEASURES

SKIN: Remove contaminated clothing and wash affected areas with soap and water. Wash contaminated clothing before reuse. If redness, itching, or a burning sensation develops, get medical attention.

EYES: Flush with clear water for 15 minutes and seek immediate medical attention.

BREATHING: Only high temperatures may generate vapors that may irritate.

SWALLOWING: Get medical attention. Do NOT induce vomiting. Wash mouth with water and give milk to drink if conscious.

SECTION 5 – FIRE & EXPLOSION HAZARD DATA

FLASH POINT (METHOD USED): 180°F Pensky Marten C.C.

FLAMMABLE LIMITS: Not established.

EXTINGUISHING MEDIA: Dry chemical; carbon dioxide; alcohol resistant foam; do not use water jet.

SPECIAL FIRE FIGHTING PROCEDURES: Full emergency equipment with self-contained breathing apparatus and full protective clothing should be worn. During a fire, irritating, toxic gasses and smoke are present from decomposition/combustion.

UNUSUAL FIRE & EXPLOSION HAZARDS: Closed container may explode when exposed to extreme heat. Use cold water spray to cool containers.

DECOMPOSITION PRODUCTS: When heated to point of decomposition, toxic oxides of nitrogen, carbon monoxide, and carbon dioxide are produced.

SECTION 6 – SPILL OR LEAK PROCEDURES

Remove ignition sources from spill area and evacuate non-essential personnel. Ventilate the area and equip clean-up crew with appropriate protective equipment. Dike or impound spilled material and control further spillage if feasible. Cover spill with absorbent material, collect and place in a clean, dry container. Handle as combustible waste.

SECTION 7 – HANDLING & STORAGE

Is combustible - avoid heat and open flames. Store between 50° and 104°F.

SECTION 8 – PERSONAL PROTECTION/EXPOSURE CONTROLS

RESPIRATORY PROTECTION (SPECIFY TYPE): Respiratory protection is not required while handling this product under normal conditions of use. Local exhaust if used indoors.

EYE PROTECTION: Safety glasses or goggles. Contact lenses should not be worn while using this product.

SKIN PROTECTION: Impermeable gloves are recommended.

OTHER PROTECTIVE EQUIPMENT: Eye wash station or fresh clean water.

PERSONAL HYGIENE: Wash contaminated clothing before re-use. Wash thoroughly after using this product.

SECTION 9 – PHYSICAL DATA

BOILING POINT (F)	437°	SPECIFIC GRAVITY (H2O=1)	1.2
VAPOR PRESSURE (21°C)	0.01 pa	PERCENT, VOLATILE BY VOLUME	40
VAPOR DENSITY (AIR=1)	>1	EVAPORATION RATE (N.B.A.=1)	<1
SOLUBILITY IN WATER	Miscible	pH at 10% solution	8.0

APPEARANCE & ODOR - Clear to slightly yellow liquid with a sweet odor.

SECTION 10 - REACTIVITY DATA

STABILITY: Stable under normal conditions.

INCOMPATIBILITY (MATERIALS TO AVOID): Oxidizing agents, copper and copper alloys.

HAZARDOUS DECOMPOSITION PRODUCTS: None unless heated to decomposition.

HAZARDOUS POLYMERIZATION: Will not occur.

CONDITIONS TO AVOID: Avoid heat and open flames - material is combustible.

SECTION 11 - TOXICOLOGICAL INFORMATION

See reference data for individual components.

SECTION 12- ECOLOGICAL INFORMATION

See reference data for individual components.

SECTION 13 - DISPOSAL CONSIDERATIONS

Dispose of in accordance with local, state and federal regulations. Do NOT heat or cut empty container with electric or gas torch.

SECTION 14 - TRANSPORT INFORMATION

PROPER SHIPPING NAME: Paint

HAZARD CLASS: 3

PACKING GROUP: 111

ID #: UN 1263

RQ: None

TRANSPORT LABELS REQUIRED: Combustible liquid. (In the U.S., this material is not regulated in containers less than 119 gallons via surface transportation.)

SECTION 15 - REGULATORY INFORMATION

See reference data for individual components.

SECTION 16- OTHER INFORMATION (HMIS RATING)

Health	1
Flammability	2
Physical Hazard	0
Personal Protection	B

This information accumulated herein is believed to be accurate but is not warranted to be, whether originating with the company or not. Recipients are advised to confirm, in advance of need, that the information is current, applicable and suitable to their circumstances. Andek Corporation assumes no legal responsibility for use of or reliance upon the information contained in this MSDS.

DATE ISSUED: OCTOBER 2007