

### SAFETY DATA SHEET

U.S. Department of Labor Occupational Safety & Health Administration

# **OZ** Catalyst

## **SECTION 1 - IDENTIFICATION**

MANUFACTURER: Andek Corporation

ADDRESS: 850 Glen Avenue, Moorestown, NJ 08057

TELEPHONE: 1-856-786-6900

In an emergency, contact CHEMTREC 1-800- 424-9300;

Outside the United States call +1-703-527-3887

PRODUCT IDENTIFIER: OZ Catalyst RECOMMENDED USE: Reinforcing Agent

### **SECTION 2 – HAZARD IDENTIFICATION**

HAZARD CLASSIFICATION (EFFECTS OF EXPOSURE):

**Skin:** May cause allergic skin reaction. **Eyes:** Causes serious eye damage.

**Inhalation:** High vapor concentrations are irritating to the respiratory tract.

**Ingestion:** Harmful if swallowed and enters airways.

SIGNAL WORD: Danger

### **HAZARD STATEMENTS:**

- Flammable liquid and vapor.
- Harmful if swallowed.
- Causes serious eye damage.
- May cause an allergic skin reaction.
- May be harmful if inhaled.

### **PICTOGRAMS:**







### PRECAUTIONARY STATEMENTS:

#### **Prevention:**

- **Do Not** handle until all safety precautions have been read and understood.
- · Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- **Do Not** breathe dust, vapors or spray.
- Do Not get in eyes, on skin, or on clothing.
- Wash thoroughly after handling.
- **Do Not** eat, drink or smoke when using this product.
- Use only outdoors or in a well-ventilated area.
- Wear protective gloves/protective clothing/eye protection/face protection.
- **Do Not** allow contact with water.

### Response:

- **Skin:** Wash with plenty of water.
- Eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do and continue rinsing.
- Inhalation: Remove person to fresh air and keep comfortable for breathing.
- **Ingestion:** Rinse mouth. **Do Not** induce vomiting.

Page 1 of 6 OZ Catalyst

#### Storage:

- Store in a well ventilated place.
- Keep container tightly closed.
- Store at temperatures between 50°F and 90°F.

#### Disposal:

- Waste disposal should be in accordance with existing federal, state and local environmental control laws.
- Incineration is the preferred method.

## **SECTION 3 – COMPOSITION**

| CHEMICAL NAME                   | CAS#        | APPROX % |
|---------------------------------|-------------|----------|
| Modified Oxazolidine            | 145899-78-1 | 90       |
| Naphtha, Light Aromatic Solvent | 64742-95-6  | 10       |

## **SECTION 4 – FIRST AID MEASURES**

#### Skin:

- Remove affected person from source of contamination.
- Remove contaminated clothing.
- Wash the skin immediately with soap and water.
- Get medical attention if irritation persists after washing.

#### Eyes:

- Remove victim immediately from source of exposure.
- Make sure to remove any contact lenses from the eyes before rinsing.
- Promptly wash eyes with plenty of water while lifting the eye lids.
- Get medical attention immediately.
- Continue to rinse

#### **Inhalation:**

- Move the exposed person to fresh air at once.
- Rinse nose and mouth with water.
- Get medical attention if any discomfort continues.

### **Ingestion:**

- Immediately rinse mouth and drink plenty of water.
- Keep person under observation.
- If person becomes uncomfortable seek hospital and bring these instructions.
- NEVER MAKE AN UNCONSCIOUS PERSON VOMIT OR DRINK FLUIDS.

### **SECTION 5 – FIRE-FIGHTING MEASURES**

### **Extinguishing media:**

- Extinguish with foam, carbon dioxide or dry powder.
- **Do Not** use water as an extinguisher.

### **Special fire fighting procedures:**

- Use air-supplied respirator during fire fighting.
- Use water SPRAY only to cool containers!
- Do Not put water on leaked material.
- Keep run-off water out of sewers and water sources.
- Dike for water control.

#### **Unusual fire & explosion hazards:**

- Decomposes slowly with water to yield isobutyraldehyde (flammable).
- In case of fire, toxic gases may be formed (COx, NOx).

### SECTION 6 – ACCIDENTAL RELEASE MEASURES

### **Personal precautions:**

- Wear protective clothing as described in Section 8 of this safety data sheet.
- Eye contact **MUST** be prevented by means of suitable personal protection equipment.

### **Emergency procedures:**

- **Do Not** allow to enter drains, sewers or watercourses.
- Spillages or uncontrolled discharges into watercourses must be IMMEDIATELY alerted to the Environmental Agency or other appropriate regulatory body.

Page 2 of 6 OZ Catalyst

#### Methods and materials used for containment:

- Absorb in vermiculite, dry sand or earth and place into containers.
- Decomposes slowly with water to yield isobutyraldehyde (flammable).
- Vapors may form explosive air mixtures even at room temperature.
- Extinguish all ignition sources.
- Avoid sparks, flames, heat and smoking.

### Cleanup procedures:

- Ventilate.
- Stop leak if possible without risk.
- Do Not contaminate water sources or sewer.
- Containers with collected spillage must be properly labeled with correct contents and hazard symbol.
- Flush with plenty of water to clean spillage area.

### **SECTION 7 – HANDLING & STORAGE**

### Precautions for safe handling:

- Avoid inhalation of vapors/spray and contact with skin and eyes.
- Decomposes slowly with water to yield isobutyraldehyde (flammable).
- Risk of vapor concentration on the floor and in low-lying areas.
- Vapors may form explosive air mixtures even at room temperature.
- Keep away from heat, sparks and open flame.

### Recommendations on the conditions for safe storage:

- Store in tightly closed original container in a dry, cool and well-ventilated place.
- Protect from freezing and direct sunlight.
- Open only when ready for use and reseal part used containers after use.
- OZ Catalyst is designed to be non-crystallizing at 25°C; however, at temperatures below 5°C it is possible for some crystallization to occur. This does not affect the quality of the product for subsequent processing and the material can be returned to its liquid state by heating to 60°C.

## SECTION 8 – EXPOSURE CONTROLS/PERSONAL PROTECTION

#### **Exposure limits:**

| CHEMICAL NAME           | PEL | TLV                |
|-------------------------|-----|--------------------|
| Cumene (Present 0.001%) | N/A | 50 ppm (TWA) 8 hr. |

### **Engineering controls:**

- Provide adequate ventilation.
- Observe Occupational Exposure Limits and minimize the risk of inhalation of vapors

### **Individual protection measures:**





**Inhalation protection**: In case of inadequate ventilation use suitable respirator.

**Eye protection**: Wear approved, tight fitting safety glasses where splashing is probable.

#### Skin and body protections:

- Use protective gloves made of: Neoprene, nitrile, polyethylene or PVC.
- Barrier cream applied before work may make it easier to clean the skin after exposure, but does not prevent absorption through the skin.

## Other hygienic practices and protective equipment:

- Provide eyewash station.
- Wear appropriate clothing to prevent any possibility of skin contact.
- Do Not Smoke In Work Area!
- Wash at the end of each work shift and before eating, smoking and using the toilet.
- Promptly remove any clothing that becomes contaminated.
- Use appropriate skin cream to prevent drying of skin.
- When using do not eat, drink or smoke.

Page 3 of 6 **OZ** Catalyst

## **SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES**

Appearance: Yellow Newtonian liquid

Physical state: Liquid Color: Yellow Odor: Sweet Pungent

Odor threshold: 0.07 ppm

pH: Alkaline

Melting point/freezing point: 45°F (7°C)

Initial boiling point and boiling range: 392°F (200°C)

Flash point: 108°F

**Evaporation rate**: 0.2 (Butyl Acetate = 1) **Flammability (solid, gas)**: Flammable

Upper/lower flammability or explosive limits: (by volume) 5.7% / 0.8%

**Vapor pressure**: 0.8 kP<sub>a</sub> (6mm Hg) @ 20°C (68°F)

Vapor density: 4 (air=1) Relative density: 1.05 kg/lt Solubility: Immiscible with water

Partition coefficient: n-octanol/water: None established

**Auto-ignition temperature**: 471°C (880°F) **Decomposition temperature**: None established

Viscosity: 200 centipoises @ 20°C

### **SECTION 10 – STABILITY AND REACTIVITY**

Chemical stability: Stable under normal temperature conditions.

Hazardous decomposition products: Fire creates: Carbon monoxide (CO) and carbon dioxide (CO<sup>2</sup>)

### Conditions to avoid:

- Avoid contact with water.
- Decomposes slowly with water to yield isobutyraldehyde (flammable).
- Vapors may form explosive air mixtures even at room temperature.

## SECTION 11 - TOXICOLOGICAL INFORMATION

Likely routes of exposure:

Oral: Irritating. May cause nausea, stomach pain and vomiting

Inhalation: In high concentrations, vapors may irritate throat and respiratory system and cause coughing

Dermal: Irritating to skin. May cause sensitization by skin contact

Eye: Risk of serious damage to eyes

Numerical measures of toxicity:

| tamerical measures of tomerty.  |                 |                       |                 |
|---------------------------------|-----------------|-----------------------|-----------------|
| CHEMICAL NAME                   | Oral LD50 (rat) | Dermal LD50           | Inhalation LC50 |
| Modified Oxazolidine            | >2000 mg/kg     | N/A                   | N/A             |
| Naphtha, Light Aromatic Solvent | 8400 mg/kg      | >3,160 mg/kg (rabbit) | 2,900 ppm (rat) |

### **SECTION 12 – ECOLOGICAL INFORMATION**

Data from toxicity test (aquatic and/or terrestrial organism where available): 5 columns

| CHEMICAL NAME    | Algae/Aquatic Plants         | Fish LC50                      | Toxicity to   | Crustacea (Aquatic         |
|------------------|------------------------------|--------------------------------|---------------|----------------------------|
|                  |                              |                                | Microorganism | Invertebrates) EC50        |
| Modified         | IC50 - 21 mg/lt (72 hr)      | 87.5 mg/lt (96 hr)             | N/A           | >100 mg/lt (Daphnia Magna) |
| Oxazolidine      | -                            | -                              |               | 48 hr                      |
| Naphtha, Light   | EC50 - <1 mg/lt (Skeletonema | 41 mg/lt (Pimephales Promelas- | N/A           | 0.95 mg/lt (Daphnia Magna) |
| Aromatic Solvent | Costatum)                    | Fathead Minnow) 96 hr          |               | 48 hr.                     |

**Biodegradation**: The product is biodegradable, but it must not be discharged into drains without permission from the waste disposal authority.

**Bioaccumulation potential**: No data available.

Mobility in soil: No data available.

Other adverse effects: Dangerous for the environment if discharged into watercourses.

Page 4 of 6 OZ Catalyst

## **SECTION 13 - DISPOSAL CONSIDERATIONS**

### Waste Disposal Method:

- Waste disposal should be in accordance with existing federal, state and local environmental control laws.
- Incineration is the preferred method.

### **Empty Container Precautions:**

- Empty containers retain product residue; observe all precautions for product.
- Do Not heat or cut empty container with electric or gas torch because highly toxic vapors and gases are formed.
- **Do Not** reuse without thorough commercial cleaning and reconditioning.
- If container is to be disposed, ensure all product residues are removed prior to disposal.

## **SECTION 14 – TRANSPORT INFORMATION**

| UN#                           | 1263                   |
|-------------------------------|------------------------|
| UN PROPER SHIPPING NAME:      | Paint                  |
| HAZARD CLASS:                 | 3                      |
| PACKING GROUP:                | III                    |
| ENVIRONMENTAL HAZARDS:        | Not a marine pollutant |
| GUIDANCE ON TRANSPORT IN BULK | N/A                    |

**Transport labels required**: Flammable liquid. (In the U.S., this material may be re-classified as a combustible liquid and is not regulated in containers less than 119 gallons via surface transportation.)

## SECTION 15 – REGULATORY INFORMATION

### **US Federal Regulation:**

### SARA 311/312 Hazard Categories

| ALLI DII/DIZ IMMUT CHOROTICA |            |            |            |                       |            |          |             |
|------------------------------|------------|------------|------------|-----------------------|------------|----------|-------------|
| CHEMICAL NAME                | CWA        | CWA        | CWA        | CWA Hazardous         | Hazardous  | CERCLA/  | Reportable  |
|                              | reportable | Toxic      | Priority   | Substances            | Substances | SARA RQ  | Quantity RQ |
|                              | quantities | Pollutants | Pollutants |                       | RQs        |          |             |
| 1,2,4-Trimethylbenzene       | N/A        | Listed     | N/A        | Chronic Health Hazard | Acute      | N/A      | N/A         |
| Xylene                       | N/A        | Listed     | N/A        | Chronic Health Hazard | Acute      | N/A      | N/A         |
| Cumene (Present 0.001%)      | 5000 lbs   | Listed     | N/A        | Chronic Health Hazard | Acute      | Required | 5000 lbs    |

US State Right to Know Regulations: New Jersey, Massachusetts, Pennsylvania, Rhode Island

| CHEMICAL NAME           | CAS #   |
|-------------------------|---------|
| 1,2,4-Trimethylbenzene  | 95-63-6 |
| Cumene (Present 0.001%) | 98-82-8 |

CA Prop 65

| CHEMICAL NAME           | CAS#    |
|-------------------------|---------|
| Cumene (Present 0.001%) | 98-82-8 |

Canada: None listed

# **SECTION 16 – OTHER INFORMATION (HMIS RATING)**

| Health              | 1 |
|---------------------|---|
| Flammability        | 2 |
| Physical Hazard     | 0 |
| Personal Protection | G |

Page 5 of 6 OZ Catalyst

| reliable as of the<br>beyond Andek<br>materials and m<br>may present un<br>consideration a | ne issue date of this<br>Corporation's contro<br>nakes no warranty, ex<br>known hazards and s | Safety Data Sheet (<br>ol, we assume no re<br>pressed or implied,<br>hould be used with a<br>s the responsibility of | SDS). However, sponsibility or lia regarding the accuration. The inform of the user to determine the second | because the condi<br>bility for personal<br>racy or reliability of<br>mation and recomi | tions of handling, use injury or property of the data or results mendations contained | n contained herein to<br>use, and storage of the<br>damage incurred by<br>obtained from their used<br>in the SDS are offer<br>mation and data and to | se materials are the use of these te. All materials and for the users |
|--|---|--|--|---|---|--|---|
|  |   |  |  |   |   |  |   |
|  |   |  |  |   |   |  |   |
|  |   |  |  |   |   |  |   |
|  |   |  |  |   |   |  |   |
|  |   |  |  |   |   |  |   |
|  |   |  |  |   |   |  |   |
|  |   |  |  |   |   |  |   |
|  |   |  |  |   |   |  |   |
|  |   |  |  |   |   |  |   |
|  |   |  |  |   |   |  |   |
|  |   |  |  |   |   |  |   |
|  |   |  |  |   |   |  |   |
|  |   |  |  |   |   |  |   |
|  |   |  |  |   |   |  |   |
|  |   |  |  |   |   |  |   |
|  |   |  |  |   |   |  |   |
|  |   |  |  |   |   |  |   |
|  |   |  |  |   |   |  |   |
|  |   |  |  |   |   |  |   |
|  |   |  |  |   |   |  |   |
|  |   |  |  |   |   |  |   |
|  |   |  |  |   |   |  |   |
|  |   |  |  |   |   |  |   |
|  |   |  |  |   |   |  |   |
|  |   |  |  |   |   |  |   |
|  |   |  |  |   |   |  |   |
| Page 6 of 6  |   |  | OZ Catalyst  |   |   |  |   |