

# **SAFETY DATA SHEET**

U.S. Department of Labor Occupational Safety & Health Administration

# Polaprime DTM

# **SECTION 1 - IDENTIFICATION**

MANUFACTURER: Andek Corporation

ADDRESS: 850 Glen Avenue, Moorestown, NJ 08057

TELEPHONE: 1-856-786-6900

In an emergency, contact CHEMTREC 1-800- 424-9300;

Outside the United States call +1-703-527-3887

PRODUCT IDENTIFIER: Polaprime DTM RECOMMENDED USE: Industrial Primer

# <u>SECTION 2 – HAZARD IDENTIFICATION</u>

HAZARD CLASSIFICATION (EFFECTS OF EXPOSURE):

Skin: No irritation hazard in normal industrial use.

**Eves:** No irritation hazard in normal industrial use.

**Inhalation:** No irritation hazard in normal industrial use.

Ingestion: Ingestion of large amounts may cause nausea and/or constipation.

Sensitization: Does not cause sensitization.

SIGNAL WORD: Warning - No hazard in normal industrial use.

**HAZARD STATEMENTS**: None

**<u>PICTOGRAMS</u>**: None Necessary

### **PRECAUTIONARY STATEMENTS:**

#### **Prevention:**

- Do Not handle until all safety precautions have been read and understood.
- **Do Not** breathe dust or spray.
- Do Not get in eyes, on skin, or on clothing.
- Wash thoroughly after handling.
- **Do Not** eat, drink or smoke when using this product.

#### Response:

- Skin: Wash affected areas thoroughly with soap and water. Wash contaminated clothing before reuse.
- Eyes: Use eyewash to remove substance from eyes. Get medical advice if irritation develops.
- Inhalation: Call a POISON CENTER/ doctor if spray or dust is inhaled
- Ingestion: Do Not induce vomiting. Get Medical advice/attention if you feel unwell; rinse mouth.

#### Storage:

- Store in a cool dry place.
- **Do Not** allow this material to freeze.

#### Disposal:

• Waste disposal should be in accordance with existing federal, state and local environmental control laws.

Page 1 of 5 Polaprime DTM

### SECTION 3 – COMPOSITION

<u>CHEMICAL NAME</u>	CAS#	APPROX %
Triethylamine	121-44-8	2.5
Polyurethane Dispersion	Trade Secret	25
Magnesium Silicate	14807-96-6	16
Magnesite	546-93-0	7
Bismuth Vanadate	14059-33-7	2.5
Diethylene Glycol Monobutyl Ether	112-34-5	3.5
2,2,4-Trimethyl-1,3-Pentanediol Monoisobutyrate	25265-77-4	3.5
Water	7732-18-5	40

# **SECTION 4 – FIRST AID MEASURES**

Skin: Wash with soap and water.

Eyes: Flush with plenty of water to remove any substance in the eyes. Remove contact lenses if present. Seek medical advice if irritation develops.

**Inhalation:** If mist (over spray) or dust (from sanding) is inhaled, move person to fresh air. If person is not breathing, call 911 or an ambulance, then give artificial respiration. Call for medical attention.

**Ingestion:** Do Not induce vomiting. Seek medical attention if symptoms develop.

### SECTION 5 – FIRE-FIGHTING MEASURES

Flash point: Non Flammable.

Flammable limits: None Established.

Extinguishing media: Water spray, foam dry chemical or carbon dioxide. Use whatever media deemed appropriate for surrounding fire.

**Special fire fighting procedures**: Persons exposed to products of combustion should wear self-contained breathing apparatus and full protective equipment.

**Unusual fire & explosion hazards**: There may be a possibility of pressure buildup in closed containers when heated. Water spray may be used to cool the containers.

**Decomposition products**: Carbon monoxide, carbon dioxide, nitrogen oxides. Thermal decomposition can lead to release of irritating gases and vapors.

### SECTION 6 – ACCIDENTAL RELEASE MEASURES

### Personal precautions:

- Wear safety glasses when handling this product.
- No adverse health effects expected from the clean-up of spilled material.

### Cleanup procedures:

- Dike if necessary, contain spill with inert absorbent and transfer to containers for disposal.
- Keep spilled product out of sewers, watersheds, or water systems.

# **SECTION 7 – HANDLING & STORAGE**

#### Precautions for safe handling:

- No special handling instructions due to toxicity.
- This product contains limited amounts of residual monomer. Under normal handling and use conditions the residual monomer should not
  present a hazard.
- In storage the monomer will migrate from the emulsion and establish equilibrium between the headspace in the storage container and the liquid emulsion.
- Levels in excess of acceptable exposures can accumulate in non-vented headspaces above the emulsion.

Recommendations on the conditions for safe storage: Store in a cool, dry place.

Page 2 of 5 Polaprime DTM

### SECTION 8 – EXPOSURE CONTROLS/PERSONAL PROTECTION:

#### **Exposure limits:**

CHEMICAL NAME	PEL	TLV (ACGIH)	NIOSH IDLH
Triethylamine	TWA: 10 ppm (OSHA);	TWA: 1 PPM Skin; STEL: 3ppm	200 ppm
Diethylene Glycol Monobutyl Ether	N/A	TWA: 10 ppm	N/A

Engineering controls: Ensure adequate ventilation, especially in confined areas, showers, eyewash stations, ventilation systems.

**Individual protection measures:** Not normally considered a significant hazard.

Inhalation protection: If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA respiratory protection should be worn.

Eye protection: Wear tightly fitting safety goggles when handling this product.

Skin and body protections: Wear protective gloves and protective clothing to avoid skin contact.

Other hygienic practices and protection equipment: Handle in accordance with good industrial hygiene and safety practice.

### **SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES:**

Appearance: Low viscosity liquid

Physical state: Liquid Color: Orange

Odor: Mild soapy odor

Odor threshold: None established

**pH:** 8.5

Melting point/freezing point: 32°F Freezing point

Initial boiling point and boiling range: 212°F Boiling point

Flash point: Non flammable Evaporation rate: 1.0 (water =1) Flammability: Non flammable

Upper/lower flammability or explosive limits: None established

**Vapor pressure**: 23 hPa (17 mmHg) @ 68°F (20°C)

**Vapor density:** 1.24 g/cm<sup>3</sup> @ 68°F (20°C)

Relative density: 1.21 kg/Lt

Solubility: Soluble with water and alcohol

Partition coefficient: n-octanol/water: None established

**Auto-ignition temperature:** None established **Decomposition temperature:** 392°F (200°C) **Viscosity:** 70 Krebs units @ 68°F (20°C)

# **SECTION 10 - STABILITY AND REACTIVITY**

Reactivity: Stable under normal conditions.

Chemical stability: Stable under recommended storage conditions.

Incompatibility: Strong oxidizing agents.

Hazardous decomposition products: Carbon monoxide, carbon dioxide, nitrogen oxides. Thermal decomposition can lead to release of irritating

gases and vapors.

Conditions to avoid: Do not freeze, coagulation of solids may occur.

#### SECTION 11 – TOXICOLOGICAL INFORMATION

The following information regarding health hazards is based upon third-party research studies.

**Effects of Acute Exposure:** 

Oral: Based on acute toxicity values, not classified.

Inhalation: No adverse effect observed.

Page 3 of 5 Polaprime DTM

**Dermal:** Based on acute toxicity values, not classified.

Effects from short and long term exposure: No known chronic effects based on supplied information.

#### Numerical measures of toxicity:

CHEMICAL NAME	Oral LD50	Dermal LD50	Inhalation
Triethylamine	460 mg/kg (rat)	415 mg/kg (rabbit)	LC50 - 1250 ppm (rat) 4 hrs.
Diethylene Glycol Monobutyl Ether	2410 mg/kg (mouse)	2764 mg/kg (rabbit)	LC0 - 2100 ppm (rat) 4 hrs.
2,2,4-Trimethyl-1,3-Pentanediol Monoisobutyrate	6500 mg/kg (rat)	15200 mg/kg (rabbit)	LC50 - 3550 ppm (rat) 6 hrs.

Symptoms associated with exposure: No Adverse effect observed.

Chemical listed in NTP or IARC: No component of this product present at levels greater than or equal to 0.1% is listed with NTP or IARC.

# **SECTION 12 – ECOLOGICAL INFORMATION**

Data from toxicity test (aquatic and/or terrestrial organism where available):

CHEMICAL NAME	Algae/Aquatic Plants -	Fish - LC50	Toxicity to	Crustacea
	ErC 50		Microorganism	(Aquatic Invertebrates)
Triethylamine	N/A	43.7 mg/l (Pimephales	N/A	200 mg/l (Daphnia magna)
		promelas) 96 hrs.		48 hrs.
2,2,4-Trimethyl-1,3-	15 mg/l	33 mg/l (Fathead	N/A	147.8 mg/l (Daphnia magna)
Pentanediol Monoisobutyrate	(Pseudokirchneriella	Minnow) 96 hrs.		48 hrs.
	subcapitata) 72 hrs.			

Biodegradation: Partially biodegradable (28 day, ready biodegradability: CO<sup>2</sup> Evolution test).

**Bioaccumulation potential:** This material is not expected to bioaccumulate.

Mobility in soil: Log Kow: 2.3 -3.2 @25°C

Other adverse effects: No additional information available

### **SECTION 13 – DISPOSAL CONSIDERATIONS**

To the best of our knowledge, this product does not meet the definition of hazardous waste under the U.S. EPA Hazardous Waste Regulations 40 CFR 261. Solidify and dispose of in an approved landfill. Consult state, local or provincial authorities for more restrictive requirements.

# **SECTION 14 – TRANSPORT INFORMATION**

UN#	N/A
UN PROPER SHIPPING NAME:	Paint
HAZARD CLASS:	N/A
PACKING GROUP:	N/A
ENVIRONMENTAL HAZARDS:	N/A
GUIDANCE ON TRANSPORT IN BULK:	N/A

Transport labels required: This product is not regulated by the D.O.T.

# **SECTION 15 – REGULATORY INFORMATION**

**US Federal Regulation:** 

SARA 311/313 Hazard Categories: None of the ingredients of this product are subject to SARA 311-313

CHEMICAL	CWA reportable	CWA Toxic	CWA Priority	CWA Hazardous	Hazardous	CERCLA/SARA	Reportable
NAME	quantities	Pollutants	Pollutants	Substances	Substances RQs	RQ	Quantity RQ
Triethylamine	5000 lbs	-	1	X	5000 lbs	-	5000 lbs

### US State Right to Know Regulations: New Jersey, Massachusetts, Pennsylvania, Rhode Island

CHEMICAL NAME	CAS #
Triethylamine	121-44-8
Diethylene Glycol Monobutyl Ether	112-34-5
2,2,4-Trimethyl-1,3-Pentanediol Monoisobutyrate	25265-77-4

Page 4 of 5 Polaprime DTM

**CA Prop 65:** This product does not contain any proposition 65 chemicals.

Canada: DSL inventory compliant.

# <u>SECTION 16 – OTHER INFORMATION (HMIS RATING)</u>

Health	1
Flammability	0
Physical Hazard	0
Personal Protection	В

**Disclaimer:** Andek Corporation believes, to the best of its knowledge, information and belief, the information contained herein to be accurate and reliable as of the issue date of this Safety Data Sheet (SDS). However, because the conditions of handling, use, and storage of these materials are beyond Andek Corporation's control, we assume no responsibility or liability for personal injury or property damage incurred by the use of these materials and makes no warranty, expressed or implied, regarding the accuracy or reliability of the data or results obtained from their use. All materials may present unknown hazards and should be used with caution. The information and recommendations contained in the SDS are offered for the users' consideration and examination. It is the responsibility of the user to determine the final suitability of this information and data and to comply with all applicable international, federal, state and local laws and regulations.

Page 5 of 5 Revision Date: 7/30/2022